



# NOX VAC 100

## **PRODUCT DESCRIPTION:-**

**LUBRINOX**<sup>(R)</sup> **NOX VAC 100** is a premium quality lubricant designed for vacuum pump. It is developed from highly refined base stocks bearing very high boiling point and low vapour pressure and selected additives to impart properties like anti-wear, anti-oxidation, anti-foaming, anti-corrosion etc. It is highly stable to chemical and oxidation degradation to resists sludge and deposit formation.

## **APPLICATIONS:-**

1) Recommended for the lubrication of vacuum pumps at an absolute pressure from 50mm/psi of mercury to the highest vacuum achieved by the pump.

#### **BENEFITS:-**

- 1) Excellent air release property.
- 2) Very good demulsibility.
- 3) Very low vapour pressure.
- 4) Provides consistent vacuum.
- 5) Longer service life.

## PRECAUTION:

Avoid prolonged and repeated contact with used oil. Used oil contains potentially harmful contaminants. Keep out of reach of children. Used oil must be disposed off carefully to prevent damage to environment.

### **AVAILABLE PACK SIZE:**

20 Ltr, 50 Ltr, 210 Ltr

## **TYPICAL CHARACTERISTICS:**

Appearance	Bright & Clear
Kin. Viscosity @ 40°C	88
Viscosity Index, min	97
Flash Point <sup>o</sup> C, COC, min	240
Pour Point <sup>o</sup> C, max	-9

\* These specifications are subject to variations/development/customisation.

