

NOX CUT NS 18

PRODUCT DESCRIPTION:

LUBRINOX^(R) NOX CUT NS 18 is light coloured EP type neat cutting oil developed from highly refined mineral base stocks and stable chlorinated EP additives and fatty materials to provide smooth metal working operation on both ferrous and non-ferrous metals.

APPLICATIONS:

- 1) Recommended for the machining of both ferrous and non-ferrous metals. It covers applications like lathe work, thread grinding, milling, turning etc.

BENEFITS:

- 1) Very good anti-chip welding properties.
- 2) Provides visibility of cutting operations.
- 3) Extended tool life.
- 4) Highly lubricity.

PRECAUTION:

Avoid prolonged and repeated contact with used oil. Used oil contains potentially harmful contaminants. Keep out of reach of children. Used oil must be disposed off carefully to prevent damage to environment.

AVAILABLE PACK SIZE:

20 Ltr, 50 Ltr, 210 Ltr

TYPICAL CHARACTERISTICS

Kin. Viscosity @ 40 ⁰ C, cst	18
Flash Point ⁰ C, COC, min	160
Copper Corrosion @ 100 ⁰ C for 3 Hrs	1b
SAP Value, Mg Kott/Gm	8

* These specifications are subject to variations/development/customisation.