



TRACTOR 1 UTTF 80W (API GL-4)

DESCRIPTION:

LUBRINOX® TRACTOR 1 UTTF 80W is a premium grade of lubricant designed to solely serve as transmission fluid, hydraulic fluid and for the oil immersed brakes of tractors and off road equipment's in a single product. It optimizes the performance of agricultural and commercial tractors serving as a common lubricant for transmission, hydraulic system and wet brakes. **LUBRINOX® TRACTOR 1 UTTF 80W** meets all the required standards of API GL-4.

APPLICATION:

- It is recommended for agricultural and commercial tractors as a common lubricant for their transmission, hydraulic system and differential.
- It is also recommended to be used in equipment's where construction, quarrying and mining are used.

BENEFITS:

- Excellent wet clutches and wet brake performance.
- Smooth gear operation.
- Superior thermo oxidative stability.
- Very good corrosion protection.

CAUTION:

Avoid prolonged and repeated contact with used engine oil. Used engine oil contains potentially harmful contaminations. Keep out of reach of children. Used engine oil must be disposed of carefully to prevent damage to environment.

TYPICAL CHARACTERISTICS:

| | |
|------------------------------|----------------|
| Appearance, visual | Bright & Clear |
| Colour, Visual | Natural |
| K. Viscosity, cst at 100 ° C | 9.6 |
| Viscosity index, mn. | Min. 140 |
| Total base no., mgKOH/gm | 9 |
| Flash point, ° C | 210 |
| Pour point, ° C | -30 |
| S. Ash, % wt. | 1.3 |

* These specifications are subject to variations/development/customization

AVAILABLE PACK SIZES: 5 LTR, 20 LTR, 50 LTR & 210 LTR