



HYDRONOX 10W

DESCRIPTION:

LUBRINOX® HYDRONOX 10W is mono-grade oil for heavy duty hydraulic oil formulated from highly refined base stocks and performance proven additives. This product is specifically developed from ash free dispersants and metallic detergents combined with inhibitors to control oxidation, wear, corrosion and rust.

APPLICATION:

- Recommended to be used in hydraulic systems containing gears and bearings where good anti-wear properties are required
- Also recommended to be used in on and off-highway applications like construction, mining, quarrying, and agriculture.

BENEFITS:

- Excellent detergent capacity.
- Excellent resistance to oxidation and ageing.
- Great antioxidant protection, anticorrosive and anti-rust.
- Excellent filterability.

CAUTION:

Avoid prolonged and repeated contact with used grease. Used grease contains potentially harmful contaminations. Keep out of reach of children. Used grease must be disposed of carefully to prevent damage to environment.

TYPICAL CHARACTERISTICS:

Appearance	Bright & Clear
Kin. Viscosity @ 100°C, cSt	5.5-7.0
Viscosity index, Min.	95
Flash point COC, Min. (°C)	200
Pour Point, Max. (°C)	-25
Sulphated ash (%wt.)	1.3
TBN (mg KOH/g)	10

* These specifications are subject to variations/development/customization

AVAILABLE PACK SIZES: 20L, 50L & 210L