

## MATERIAL SAFETY DATA SHEET

### (TRACTOR MAGIC 20W40)

#### 1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : TRACTOR MAGIC 20W40  
USE : DIESEL ENGINE OIL  
COMPANY NAME : K.B. LUBES PVT. LTD.  
CONTACT NO. : 020- 27641110/ 08552981455

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture of refined mineral oil and additives

#### 3. HAZARDS IDENTIFICATION

- Prolonged exposure can cause skin irritation
- Keep out of sewers and waterways
- May cause irritation

#### 4. FIRST AID MEASURES

EYE : Flush with water. If irritation persists contact for  
Medical assistance

SKIN : Wash with soap and water.

INGESTION : DO NOT INDUCE VOMITTING. Get medical Assistance.

INHALATION : Take fresh air. Get medical assistance if discomfort  
Persists.

# Lubrinol™



## **5) FIRE FIGHTING MEASURE**

Flash Point	: < 200 degC.
Extinguishing media	: Dry chemical, CO2, Water fog, foam
Decomposition Products	: May cause dense smoke, oxides of carbon

## **6. HANDLING AND STORAGE**

Avoid eye and prolonged skin contact with all industrial material. Wash thoroughly after handling. Follow all MSDS. Keep containers closed when not in use.

## **7) PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: Bright and clear
Odour	: Mild
Viscosity, cst at 100 degC.	: 14.5 – 15.5
Flash Point, degC.	: < 200
Vapour pressure	: Not detected
Solubility in water	: 0

## **8) STABILITY AND REACTIVITY**

Hazardous decomposition products	: May cause dense smoke, oxides of carbon
Chemical stability	: Stable at room temperature and pressure
Conditions to avoid	: Excessive heat or flame
Incompatibility	: Oxidizing or acidic materials
Hazardous polymerization	: Will not occur

## **9) DISPOSAL CONSIDERATION**

Any disposal practice must be in compliance with local , state and federal laws and regulations.

\*\*\*\*\*