

NOX COM 100 & 150

PRODUCT DESCRIPTION:

LUBRINOX^(R) NOX COM 100 & 150 are high quality compressor oils developed for reciprocating compressors. These are developed from highly stable base stocks and selected additives. These compressor lubricants provide excellent performance in compressor operating at high discharge temperature up to 210⁰C. These lubricants reduce carbon deposition on piston rings and exhaust valves and provide proper lubrication to the cylinders.

APPLICATIONS:

- 1) Recommended for reciprocating sliding van and screw compressors.

BENEFITS:

- 1) Excellent protection against wear
- 2) Reduces carbon deposition.
- 3) Highly stable against thermal cracking and oxidation.
- 4) Performs at high discharge temperature.
- 5) Reduces maintenance cost.

PRECAUTION:

Avoid prolonged and repeated contact with used oil. Used oil contains potentially harmful contaminants. Keep out of reach of children. Used oil must be disposed off carefully to prevent damage to environment.

AVAILABLE PACK SIZE:

20 Ltr, 50 Ltr, 210 Ltr

TYPICAL CHARACTERISTICS:

ISO VG GRADES	100	150
Kin. Viscosity @ 40 ⁰ C, cst	96	144
Viscosity Index, min	95	95
Flash Point ⁰ C, COC, min	220	228
Pour Point, ⁰ C, max	-6	-6
Copper Corrosion @100 ⁰ C for 3 hours	1b	1b

* These specifications are subject to variations/development/customisation.