

NOX QUENCH 30

PRODUCT DESCRIPTION:

LUBRINOX^(R) NOX QUENCH 30 is premium quality quenching oil developed from highly refined, thermal stable, high viscosity index base oils with very good oxidation stability and low volatility.

APPLICATIONS:

- 1) Recommended for all normal quenching operations on a wide variety of steels.
- 2) This is normally used for the hardening of nuts, bolts and ball bearings.
- 3) It is always recommended to keep the oil bath temperature not more than 60⁰C for the best results and longer oil life.

BENEFITS:

- 1) Provides uniform hardness.
- 2) No metallurgical distortion.
- 3) Very good oxidation stability.
- 4) Longer service life.
- 5) Satisfactory quenching results.

PRECAUTION:

Avoid prolonged and repeated contact with used oil. Used oil contains potentially harmful contaminants. Keep out of reach of children. Used oil must be disposed off carefully to prevent damage to environment.

AVAILABLE PACK SIZE:

20 Ltr, 50 Ltr, 210 Ltr

TYPICAL CHARACTERISTICS:

Kin. Viscosity @ 40 ⁰ C, cst	30
Viscosity Index, Min	95
Flash Point ⁰ C, COC, min	219
Pour Point ⁰ C, max	-6
Copper Corrosion at 100 ⁰ C for 3 hrs	1b

* These specifications are subject to variations/development/customisation.