

TURBONOX 46 & 68 (IS : 1012 : 1987)

DESCRIPTION:

LUBRINOX^(R) TURBONOX SERIES are high quality turbine lubricants formulated from high quality, very high viscosity index base stock and performance proven selected additives to provide outstanding service life. These oils provide excellent corrosion prevention, demulsibility and anti-wear properties.

APPLICATIONS:

- 1) These turbine lubricants are recommended for a wide variety of applications which includes central power station turbo-generators, gas turbines, hydraulic application, air line lubricators etc.

BENEFITS:

- 1) Provides life more than 6000 hrs.
- 2) Very good protection against corrosion.
- 3) Very low deposits.
- 4) Excellent demulsibility.
- 5) Reduces maintenance cost.

PRECAUTION:

Avoid prolonged and repeated contact with used oil. Used oil contains potentially harmful contaminants. Keep out of reach of children. Used oil must be disposed off carefully to prevent damage to environment.

AVAILABLE PACK SIZE:

20 Ltr, 50 Ltr, 210 Ltr

TYPICAL CHARACTERISTICS:

ISO VG GRADE	46	68
Kin. Viscosity @ 40°C, CST	44	68
Viscosity Index, min	105	100
Flash Point°C, COC, min	214	218
Pour Point, °C, max	-9	-9
Rust Test, D 665	Passes	Passes

* These specifications are subject to variations/development/customisation.