



LGO EP (IS 8406: 1993, API GL-4)

DESCRIPTION:

LUBRINOX™ LGO EP series are premium quality EP gear oil formulated from solvent refined base stocks and performance proven sulphur phosphorous based EP additives to provide excellent EP properties, antifoaming, anti-corrosion and other important characteristics.

APPLICATION:

1. Recommended for use in all types of industrial enclosed gear drives operating under high load conditions.

BENEFITS:

1. Excellent extreme pressure properties.
2. Very good thermo-oxidative stability.
3. Superior anti foaming properties.
4. Very good anti -wear characteristics.

PRECAUTION:

Avoid prolonged and repeated contact with used oil. Used oil contains potentially harmful contaminants. Keep out of reach of children. Used oil must be disposed off carefully to prevent damage to environment.

AVAILABLE PACK SIZE:

20 Ltr, 50 Ltr, 210 Ltr

TYPICAL CHARACTERISTICS:

ISO VG GRADE	100	150	220	320	460
Appearance	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear	Bright & Clear
Kin. Viscosity, @ 40 ⁰ C, cst	100	150	220	320	460
Viscosity index , min.	95	95	95	95	95
Flash, COC , ⁰ C ,min.	210	220	224	230	240
Pour point ⁰ C , max	-6	-6	-6	-6	-6
Copper strip corrosion @ 100 ⁰ C, for 3 hrs	1b	1b	1b	1b	1b
Foaming characteristics :					
Sequence I	NIL	NIL	NIL	NIL	NIL
Sequence II	NIL	NIL	NIL	NIL	NIL
Sequence III	NIL	NIL	NIL	NIL	NIL

*These specifications are subject to variations/development/customisation.