

NOX SPIN 12 & 22

PRODUCT DESCRIPTION:-

LUBRINOX^(R) NOX SPIN 12 & 22 are high quality spindle lubricants which bear very low pour, high viscosity index, good anti-wear and friction modifier characteristics to provide excellent performance in normal and high speed spindle in different industries.

APPLICATIONS:

- 1) Recommended for normal to high speed spindles in machine tools and textile industries.

BENEFITS:

- 1) Excellent thermo-oxidation stability.
- 2) Good chemical stability.
- 3) Prevents corrosion.
- 4) Reduces friction.
- 5) Reduces power consumption.

PRECAUTION:

Avoid prolonged and repeated contact with used oil. Used oil contains potentially harmful contaminants. Keep out of reach of children. Used oil must be disposed off carefully to prevent damage to environment.

AVAILABLE PACK SIZE:

20 Ltr, 50 Ltr, 210 Ltr

TYPICAL CHARACTERISTICS:

ISO VG GRADE	12	22
Kin. Viscosity @ 40 ⁰ C, CST	11	21
Appearance	Clear Liquid	Clear Liquid
Viscosity Index, min	100	100
Flash Point ⁰ C, COC, min	160	180
Pour Point, ⁰ C, max	-12	-09

*These specifications are subject to variations/development/customisation.