



GASO-NOX 20W-50 (API SF/CD)

DESCRIPTION:

LUBRINOX® GASO-NOX 20W-50 is excellent quality engine oil specially developed for the vehicles operating on CNG, LPG and Dual Fuel. It is highly stable to thermal and oxidation process even under operation in severe conditions. **LUBRINOX® GASO-NOX 20W-50** meets the requirements as per standards of API SF/CD.

APPLICATION:

- Recommended for use in buses, taxis, cars and 4 stroke auto-rickshaws operating on CNG, LPG or dual fuel.

BENEFITS:

- Superior oxidation and nitration resistance improves oil life.
- Prolonged valve and spark plugs life due to reduced ash.
- Smoother engine operation.
- Reduced oil consumption
- Suitable for all climatic conditions.

CAUTION:

Avoid prolonged and repeated contact with used engine oil. Used engine oil contains potentially harmful contaminations out of reach of children. Used engine oil must be disposed off carefully to prevent damage to environment.

TYPICAL CHARACTERISTICS:

Appearance	Bright & clear
Kin. Viscosity,@ 100 ^o C, cst	19
Viscosity index, min	120
Flash point, coc, °C	200
Pour point °C,max	-30

* These specifications are subject to variations/development/customization

AVAILABLE PACK SIZES: 500 ML, 1 LTR, 3 LTR, 5 LTR, 50 LTR & 210 LTR