



LLR SUPER 20W-40 (API CF-4)

DESCRIPTION:

LUBRINOX® LLR SUPER 20W-40 is excellent diesel engine oil formulated to provide outstanding engine protection by reducing friction at higher engine temperature and ultimately extends engine life. It maintains firm lubricant film even in severe operation which provides protection to the engine components from wear and tear. Its thermo-oxidative stability reduces the rate of oxidation and hence provides longer drain period. **LUBRINOX® LLR SUPER 20W-40 CF-4** meets all the required standards of API CF-4.

APPLICATIONS:

- LLR SUPER 20W-40 is recommended for use in turbo charged & naturally aspirated diesel engine working on and off road for medium to heavy duty vehicles & machineries.

BENEFITS:

- Reduces oil thickening.
- Provides smoother engine operation.
- Extends engine life by protecting its components from wear and corrosion.
- Keeps engine clean.
- Provides smoother engine operation in severe climatic conditions.

CAUTION:

Avoid prolonged and repeated contact with used engine oil. Used engine oil contains potentially harmful contaminations. Keep out of reach of children. Used engine oil must be disposed off carefully to prevent damage to environment.

TYPICAL CHARACTERISTICS:

Appearance	Red
Kin. Viscosity,@ 100° C, cst	14-15.5
Viscosity index, min	110
Flash point, coc, ° C,min	210
Pour point ° C,max	-21

* These specifications are subject to variations/development/customization

AVAILABLE PACK SIZES: 500ML, 1 LTR (CAN+POUCH), 3.5 LTR, 5 LTR, 7.5 LTR, 10 LTR, 15 LTR, 20 LTR, 50 LTR & 210 LTR