



TURBO POWER 15W-40 (API CF-4)

DESCRIPTION:

LUBRINOX® TURBO POWER 15W-40 CF-4 is heavy duty diesel engine oil developed from highly refined base stocks and performance proven additives to exhibit highest level of performance under severe operating conditions in turbo charged or naturally aspirated diesel engines. Its special additive technology provides improved protection against wear and deposits. **LUBRINOX® TURBO POWER 15W-40 CF-4** meets all the required standards of API CF-4.

APPLICATION:

- Recommended for turbo charged and naturally aspirated diesel engine of all leading manufacturers where the engine oil requirements is API CF-4.

BENEFITS:

- Superior thermo-oxidative stability which reduces sludge formation and deposits.
- Excellent corrosion and wear protection.
- Easy engine startup.
- Remove harmful soot particles from metal surfaces.
- Neutralizes harmful acids.

CAUTION:

Avoid prolonged and repeated contact with used engine oil. Used engine oil contains potentially harmful contaminations. Keep out of reach of children. Used engine oil must be disposed off carefully to prevent damage to environment.

TYPICAL CHARACTERISTICS:

Appearance	Bright & clear
Kin. Viscosity,@ 100 ^o C, cst	14-15.5
Viscosity index, min	130
Flash point, coc, ^o C	210
Pour point ^o C,max	-24
Sulphated ash,% wt	1.02

* These specifications are subject to variations/development/customization.

AVAILABLE PACK SIZES: 500 ML, 1 LTR, 3 LTR, 3.5 LTR, 5 LTR, 7.5 LTR, 10 LTR, 15 LTR, 20 LTR, 50 LTR & 210 LTR